



BXL
DISTRIBUTORS LTD.

plastic substrates

for the graphic arts industry since 1970

White Low Tack Vinyl

PRODUCT DATA SHEET

A 3.4 mil matte white flexible calendared vinyl film coated with low tack removable acrylic pressure sensitive adhesive on a 90# layflat liner. This film is designed to accept a variety of UV curable and solvent-based screen inks and is available topcoated for use with flexographic, offset and letterpress inks but must be tested prior to use.

- Applications:** This product is designed for temporary decals applied to windows.
- Thickness:** Film 3.4 mils.
Adhesive 0.8 to 1.0 mil.
Liner 6.7 mils.
(Thickness variation +/- 10%)
- Dimensional Stability:** Good.
- Temperature Ranges:** Minimum application temperature is +40°F.
Service temperature is -40°F to +200 F.
- Exterior Exposure:** Removable up to 1 year under normal conditions.
Adhesion To glass 5 to 15 oz. / in.
To standard test panels 5 to 15 oz. /in.
Tested according to PSTC-1 with 24 hour dwell at 70°F and 50% relative humidity.
Typical values. Individual values may vary. Test thoroughly before production.
- Water Resistance:** Limited immersion resistance. Test for specific application.
- Humidity Resistance:** Good.
- Storage Stability:** 6 months shelf life when stored at 70°F and 50% relative humidity.

Product data is subject to prior testing.