



BXL
DISTRIBUTORS LTD.

plastic substrates

for the graphic arts industry since 1970

Indigo Coated Low Tack Vinyl

3.4-mil top coated premium white matte flexible calendared PVC film coated with removable acrylic pressure sensitive adhesive laminated to a 90# layflat liner. This film is designed to be print receptive to the HP Indigo printers. The specialized 90# layflat liner offers excellent stability resulting in consistent printing in all environments

Applications	Designed for temporary interior signage, decals, nameplates, photo related graphics, product I.D. labels and point-of-purchase displays.
Thickness	Film 3.4 mils. Adhesive 0.8 -1.0 mils. Liner 6.7 mils. (Thickness variance +/- 10%)
Grammage/Basis Weight Caliper/Microns	299.3/ 183.8 11.7/ 297.2
Dimensional Stability	Good.
Temperature Ranges	Minimum application temperature is +40°F. Service temperature is -40°F to +180°F.
Expected Exterior Exposure	Removable up to 1 year under normal conditions.
Adhesion	To glass 5 to 15 oz. /in. To standard test panels 5 to 15 oz. /in. Tested according to PSTC-1 with 24-hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.
Water Resistance	Good. Test if immersed.
Humidity Resistance	Good.
Solvent Resistance	Good
Storage Stability	12-month shelf life when stored at 70°F and 50% relative humidity.
Product Codes	Sheet size (12" x 18") Packaging options: 100 ea.
Recommendations	Completely dry Indigo inks before application. Failure to do so may facilitate Ink penetration resulting in vinyl degradation. Certified and approved hp Indigo printers include the 3000, 3500, 5000, 5500.